

Portable Series

TOP ENTRY MIXERS



DESCRIPTION

Hayward Gordon's wide range of mixers includes a compact and rugged series of portable units. Models offered include clamp or fixed mounted with a variety of shaft sealing systems for closed tank applications and different metallurgy or coatings for corrosive or abrasive service.

FEATURES:

- 1/4 to 3 HP.
- Electric or air driven.
- Sturdy one piece housing construction.
- Lubricated for life gearing and bearings.
- Delivery from stock.
- Precision quill for rigid fixing of shaft while allowing easy replacement. Chuck mount option available.
- Direct or gear driven (1750, 1150 or 350 RPM).

DC-14	DC-13	DC-14	DC-14	DC-14	DC-12	DC-14	DC-13	DC-14	DC-14	DC-12	DC-14	DC-13	DC-14	DC-12	DC-13	DC-14	DC-13	
GC-14	GC-14	GC-13	GC-34	GC-13	GC-12	GC-12	GC-34	GC-15	GC-14	GC-14	GC-13	GC-34	GC-11	GC-13	GC-12	GC-12	GC-34	GC-15
GC-2	GC-14	GC-14	GC-13	GC-34	GC-11	GC-15	GC-13	GC-12	GC-12	GC-34	GC-15	GC-2	GC-3	GC-14	GC-14	GC-13	GC-34	GC-11
GC-15	GC-2	GC-13	GC-12	GC-12	GC-34	GC-15	GC-2	GC-3	GC-14	GC-14	GC-12	GC-34	GC-11	GC-15	GC-2	GC-3	GC-13	GC-12
GC-12	GC-11	GC-15	GC-2	GC-3	GC-14	GC-14	GC-12	GC-34	GC-11	GC-15	GC-2	GC-3	GC-12	GC-12	GC-11	GC-15	GC-2	GC-3
GC-14	GC-12	GC-34	GC-11	GC-15	GC-2	GC-3	GC-12	GC-11	GC-15	GC-2	GC-3	GC-13	GC-12	GC-34	GC-15	GC-2	GC-3	GC-34
GC-11	GC-15	GC-3	GC-12	GC-34	GC-11	GC-15	GC-3	GC-11	GC-15	GC-2	GC-3							

Propeller Spacing of 2 (two) propeller diameters is recommended for GC units.
Propeller Spacing of 4 (four) propeller diameters is recommended for DC units.
Blend Times (B.T.) shown are approximate, and are based on blending a pure fluid as opposed to two components with different viscosities.



Process Solutions since 1952

CANADA

6660 Campobello Road
Mississauga, Ontario L5N 2L9
Tel (905) 567-6116
Fax (905) 567-1706

U.S.A

1051 Clinton Street
Buffalo, New York 14206
Tel (716) 856-4636
Fax (905) 567-1706

WESTERN U.S.A.

WESTERN CANADA

Tel (604) 986-8764
Fax (604) 986-8794

E-mail: mixers@haywardgordon.com or visit our website at: www.haywardgordon.com